



Battery Watering Technologies

Aqua Sub™

25 Gallon Battery Watering Cart - NC5250PN

The Aqua Sub™ is an industrial and heavy duty watering cart. Great for filling batteries in medium and large fleets, the four-wheeled configuration rolls easily and its steel frame makes it extremely durable. With the large opening, the Aqua Sub™ is easy to fill and there are no power cords to trip over. The direct fill link on the hose delivers the right amount of pressure required to fill the batteries quickly and efficiently.



Aqua Sub™

Part# NC5250PN - 25 gallon battery watering cart with 09FBLUT3 connector

25 Gallon (95 L) Capacity - Sturdy polypropylene tank is corrosion resistant and has a large lid for easy filling. For best results, fill tank with tap water, bottled water or deionized water from the deionizer. (Deionizer Part# PW-1800)

Steel Frame - Rugged steel construction with tough powder coat finish.

Battery - Requires a 12-volt Group 24 deep cycle battery (not included).

Charger - The charger is installed inside the battery box and is intended for a 120V/60Hz AC wall outlet. The charger shuts off when the battery reaches full charge. Contact us if AC voltage requirements are different.

Direct Fill Link - Ships with a pressure regulator and 09FBLUT3 connector. It is also available with 09GRF1 or 09FUM1 connector upon request.

Manual Watering Gun - Available upon request for manual watering (Part# NC5250PN-MAN)

Hose - 12' (3.65 m) of 3/8" (9.5 mm) industrial strength hose is included.

Pump - 2.2 G.P.M. diaphragm pump with in-line fuse.

Wheels - 5" (127 mm) heavy duty industrial wheels.

Assembly - Attach handle and install battery. Everything else is pre-assembled.

Shipping Box Dimensions - 40" x 48" x 29"
(1016 mm x 1219 mm x 736 mm)

Approximate Shipping Weight Empty - 115 lbs. (52 kg)
Palletized for shipping (LTL).

Warranty - 1 year parts and labor.



Battery Watering Technologies

Aqua Sub Jr.™

9 Gallon Battery Watering Cart - NC5090PN

The Aqua Sub Jr.™ is lightweight and durable! Great for small and medium jobs, the two-wheeled configuration handles like a piece of luggage. It rolls easily and its flexibility makes it easy to maneuver. The Aqua Sub Jr.™ is easy to transport and there are no power cords to trip over. The direct fill link on the hose delivers the right amount of pressure required to fill the watering systems quickly and efficiently.



Aqua Sub Jr.™

Part# NC5090PN - 9 gallon battery watering cart with 09FBLUT3 connector

9 gallon (34 L) Capacity - Polypropylene tank is sturdy, corrosion-resistant and has a large lid for easy filling. For best results, fill tank with tap water, bottled water or deionized water from the deionizer. (Deionizer Part# PW-1800)

Collapsible Handle - The Aqua Sub Jr.™ is portable and easy to transport. Heavy duty handle is easily secured using locking pins.

Battery - 12 volt battery is included and mounted under the tank.

Charger - Matching charger plugs into a 100-240 VAC 50/60 Hz volt power supply. The charger shuts off when the battery reaches full charge. Contact us if AC voltage requirements are different.

Direct Fill Link - Ships with a pressure regulator and 09FBLUT3 connector. Competitor connectors available upon request.

Manual Watering Gun - Available upon request for manual watering (Part # NC5090PN-MAN).

Hose - 8' (2.4 m) of $\frac{3}{8}$ " (9.5 mm) braided hose is included.

Pump - 1.0 G.P.M. diaphragm pump with in-line fuse.

Wheels - Large wheel base makes it easy to maneuver. Wheel size: 11 $\frac{3}{4}$ " (298 mm)

Assembly - Use locking pins to secure handle.

Shipping Box Dimensions - 26.5" x 19" x 22.5" (673 mm x 483 mm x 558 mm)

Approximate Shipping Weight Empty - 39 lbs. (18 kg)

Warranty - 1 year parts and labor.